



## SOFT MARBLE 3053 ■ ■ FULLY MADE IN ITALY

COMPOSITION: 49%VI 39%CO 12%PL  
 HAIR: 100%VI  
 WIDTH: 140 cm  
 WEIGHT: 620-630 gr/mtl

USE: 

CARE:   
 IRON ON REVERSE

ABRASION RESISTANCE MARTINDALE END POINT: 30.000 rubs  
 UNI EN ISO 12947-2:2000 12 kPa

COLOUR FASTNESS TO LIGHT: 5  
 UNI EN ISO 105-B02:2004

COLOUR FASTNESS TO CROKING: dry 5 - wet 4/5  
 UNI EN ISO 105:X12

COLOUR FASTNESS TO WATER WASHING: 4/5  
 UNI EN ISO 105 C06:99

TENSILE STRENGTH - Strip method B: Average breaking load  
 UNI EN ISO 13934-1:2013 Warp 490 N  
 Weft 340 N

Average breaking elongation  
 Warp 14%  
 Weft 13%

COLOUR FASTNESS TO DRY CLEANING: Colour change 5  
 (perchloroethylene solvent) AC 4/5  
 UNI EN ISO 105 D01:2010 CO 4  
 PA 4

PL 4/5  
 PC 4/5  
 WO 4/5

COLOUR FASTNESS TO WATER: Colour change 5  
 UNI EN ISO 105 E01:2013 AC 4/5  
 CO 4/5

PA 4/5  
 PL 4/5  
 PC 4/5  
 WO 5

CHARACTERISTICS: viscose velvet - plain velvet - flamed effect  
 MINIMUM ORDER QUANTITY: 1 mt  
 CUSTOMISED COLOUR: 90 mt

### FLAMEPROOF TESTS

**GB** BS5852-1:1979 Cigarette using filling material  
 PU non FR (20-22 Kg/m<sup>3</sup>) SS20

**EN** EN 1021-1:2006 Cigarette EN 1021-2:2006 using filling material  
 PU FR HR30S (30-33 K/m<sup>3</sup>)

All intellectual property rights in our design and in innovative structure yarn and finishing are and will remain the property of Decobel srl. any infringement of this rights will be pursued vigorously.

